

This won't take long.



We're here to help.

Web Support

Please visit our website at www.plxdevices.com or join our support forum at www.plxdevices.com/forum/

E-Mail Support

Send messages to support@plxdevices.com

Telephone Support

Technical Support will answer technical and troubleshooting questions regarding your Kiwi Wifi during normal business hours. +1 (408)745-7591

Step 1:

Connect the OBDII cable to your vehicle's OBDII port



0:15



Step 2:

Go to settings on your iPhone/iPod Touch



0:28



Step 3:

Go to Wi-Fi setup menu



0:35



Step 4:

Turn on Wi-Fi and connect to PLXDevices



0:45

Switch the WiFi to the ON position. Tap on PLXDevices and then tap on the blue right arrow.

Tap on static and enter 192.168.0.11 into the IP Address field and 255.255.255.0 into the Subnet Mask field. Leave all other settings blank.

Step 5:

Connect the PLX iMFD serial stream to the input of the Kiwi Wifi + iMFD



You're done!

Depending on the application you use, you may be asked to enter the following information.

IP Address: 192.168.0.10
Subnet: 255.255.255.0
Port: 35000



Kiwi Wifi is compatible with Rev, DashCommand and FUZZYCar. Download them today.

Times may vary depending on how excited you are to use the Kiwi Wifi.